



SEAL APPLICATION CHART

Type	Seal Profile		Joint Gap Dimensions		Actual Movement Capability		Total
	Width	Depth	Width	Depth	Min. A	Max. A	
HS-100	1 (25)	1 1/4 (32)	1 (25)	1 3/4 (44)	3/4 (19)	1 3/8 (35)	5/8 (16)
HS-150	1 1/2 (38)	1 7/8 (48)	1 1/2 (38)	2 1/2 (64)	1 (25)	2 (51)	1 (25)
HS-200	2 (51)	2 1/2 (64)	2 (51)	3 1/4 (83)	1 (25)	2 5/8 (67)	1 5/8 (41)
HS-250	2 1/2 (64)	3 1/8 (79)	2 1/2 (64)	3 3/4 (95)	1 3/8 (35)	3 1/8 (79)	1 3/4 (44)
HS-300	3 (76)	3 7/8 (98)	3 (76)	4 1/2 (114)	1 5/8 (41)	3 3/4 (95)	2 1/8 (54)

BOLD NUMBERS INDICATE INCHES. LIGHT NUMBERS INDICATE MILLIMETERS.

NOTE:
THE ES-SERIES PROFILES
COMPLY WITH ADA GUIDELINES.



WEB: WWW.SMID.CA E-MAIL: INFO@SMID.CA

ES-SERIES ELASTIC SEAL SYSTEM SLAB TO SLAB DETAIL

Title	Date	Scale	Drawn By	Checked By	Dwg No
	JUL '05	NTS	WK	CS	TD-ES-01

REVISIONS

No.	Description	By	Date

The information contained herein is the proprietary property of SMID SYSTEMS INC. No portion of it may be reproduced by any means or used in any form except for the purpose for which it was furnished. All rights of design and invention are hereby reserved.